

UX EPR/LSOH MUD RESISTANT EARTH 600/1000V NEK606 P15/108

HALOGEN FREE, FLAME RETARDANT, EARTH CABLE



CABLE DESCRIPTION

Tinned Copper Class 2 or 5 Conductors, EPR insulated, LSOH Mud Resistant GREEN/YELLOW ; NEK606; IEC60754 1-2 ; IEC60754 1-2 ; IEC61034 1-2; IEC60332-1 IEC60332-3 CAT A

APPLICATION

Unarmoured earth cable used for fixed installations in all areas and on open deck in ships and offshore units

CSWL Part No	No Cores	Size mm ²	OD (mm) Nominal	Weight KG/KM
CSW6MM1CUXGREEN/YELLOW	1	6	5.5	81
CSW10MM1CUXGREEN/YELLOW	1	10	6.5	125
CSW16MM1CUXGREEN/YELLOW	1	16	7.5	182
CSW25MM1CUXGREEN/YELLOW	1	25	9.5	282
CSW35MM1CUXGREEN/YELLOW	1	35	10.5	371
CSW50MM1CUXGREEN/YELLOW	1	50	12.5	521
CSW70MM1CUXGREEN/YELLOW	1	70	14.5	731
CSW95MM1CUXGREEN/YELLOW	1	95	16.5	972
CSW120MM1CUXGREEN/YELLOW	1	120	18.5	1220
CSW150MM1CUXGREEN/YELLOW	1	150	20.5	1520
CSW185MM1CUXGREEN/YELLOW	1	185	22.5	1895
CSW240MM1CUXGREEN/YELLOW	1	240	26.0	2460
CSW300MM1CUXGREEN/YELLOW	1	300	29.0	3100

A Dron & Dickson Group Company

Cable Solutions

WORLDWIDE