

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Data transmission cables and systems**

with type designation(s)

MGD cat 3, MGD cat 5, cat 5e, MGD cat 6, cat 6A, MGD cat 7, 7A, MGD 1200 MHz

Issued to

TELDOR Cables & Systems Ltd.**Israel, Israel**

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft**Application :****Cable suitable for horizontal floor wiring****Products approved by this certificate are accepted for installation on all vessels classed by DNV GL.**Issued at **Høvik** on **2019-11-21**for **DNV GL**This Certificate is valid until **2024-09-26**.DNV GL local station: **Haifa**Approval Engineer: **Ivar Bull****Trond Sjøvåg**
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-032576-1**
 Certificate No: **TAE00000GE**
 Revision No: **2**

Product description

Cables suitable for horizontal floor wiring.

Cable types	Design standards	Cross section	Conductor type ref IEC 60228	Shielding
MGD cat 3, 5	IEC 61156-2	24 AWG(0.204mm ²)	Solid class 1	F/UTP, U/FTP, F/FTP, S/FTP, SF/UTP, SF/FTP
MGD cat 5e	IEC 61156-5	24 AWG(0.204mm ²)	Solid class 1	F/UTP, U/FTP, F/FTP, S/FTP, SF/UTP, SF/FTP
MGD cat 6	IEC 61156-5	23 AWG(0.246mm ²) 22 AWG(0.324mm ²)	Solid class 1	F/UTP, U/FTP, F/FTP, S/FTP, SF/UTP, SF/FTP
MGD cat 6A, 7, 7A	IEC 61156-5	23 AWG(0.246mm ²) 22 AWG(0.324mm ²)	Solid class 1	U/FTP, F/FTP, S/FTP, SF/FTP
MGD 1200MHZ	IEC 61156-7	23 AWG(0.246mm ²) 22 AWG(0.324mm ²)	Solid class 1	U/FTP, F/FTP, S/FTP, SF/FTP

Construction

Conductor	Bare annealed copper or tinned copper class 1
Insulation	Solid or cellular Polyolefine
Individual screen	*/FTP cables have individual foil screen
Common screen	S/*TP cables have a common braid screen F/*TP cables have a common foil screen SF/*TP cables have a common foil screen and a braid screen
Outer sheath	SHF1, SHF2 or SHF2 MUD, single or double layer

Optional Constructions:

- Cat3 to Cat 5e cables:
 Single cables: 4-25 Pair cables
 Multi cables: 2-12 cores or jacketed cables cabled together
- Cat 6 to 1200MHz Cables:
 Single cables: 4 Pair cables
 Multi cables: 2-12 cores or jacketed cables cabled together

Electrical data at 20°C

Category 3		
Frequency MHz	Attenuation dB/100m	NEXT dB
1	2.6	41
4	5.6	32
10	9.8	26
16	13.1	23

Category 5		
Frequency MHz	Attenuation dB/100m	NEXT dB
1	2.1	62
4	4.3	53
10	6.6	47
16	8.2	44
20	9.2	42
31.25	11.8	40
62.50	17.1	35

100	22.0	32
-----	------	----

Category 5e		
Frequency MHz	Attenuation dB/100m	NEXT dB
1	2.1	65
4	4.1	56
10	6.5	50
16	8.3	47
20	9.3	46
31.25	11.7	43
62.50	17.0	38
100	22.0	35

Category 6

Job Id: **262.1-032576-1**
 Certificate No: **TAE00000GE**
 Revision No: **2**

Frequency MHz	Attenuation dB/100m	NEXT dB
1	2.0	75.3
4	3.8	66.3
10	6.0	60.3
16	7.6	57.2
31.25	10.7	52.9
62.5	15.4	48.4
100	19.8	45.3
150	24.7	42.7
200	29.0	40.8
250	32.8	39.3

Category 6A		
Frequency MHz	Attenuation dB/100m	NEXT dB
1	2.0	75.3
4	3.8	66.3
10	5.9	60.3
16	7.5	57.2
31.25	10.5	52.9
62.5	15.0	48.4
100	19.1	45.3
150	23.7	42.7
200	27.6	40.8
250	31.1	39.3
300	34.3	38.1
400	40.1	36.3
500	45.3	34.8

Category 7		
Frequency MHz	Attenuation dB/100m	NEXT dB
1	2.0	78.0
4	3.7	78.0
10	5.9	78.0
16	7.4	78.0
31.25	10.4	78.9
62.5	14.9	75.5
100	19.0	72.4
150	23.6	69.8
200	27.5	67.9
250	31.0	66.4

300	34.2	65.2
400	40.0	63.4
500	45.3	61.9
600	50.1	60.7

Category 7A		
Frequency MHz	Attenuation dB/100m	NEXT dB
1	2.1	78.0
4	3.7	78.0
10	5.8	78.0
16	7.3	78.0
31.25	10.3	78.0
62.5	14.6	78.0
100	18.5	78.0
150	22.8	76.0
200	26.5	74.0
250	29.7	72.5
300	32.7	71.2
400	38.0	69.4
500	42.8	67.9
600	47.1	66.7
1000	61.9	63.4

1200 MHz		
Frequency MHz	Attenuation dB/100m	NEXT dB
1	1.9	78.0
4	3.5	78.0
10	5.4	78.0
16	6.8	78.0
31.25	9.6	78.0
62.5	13.7	78.0
100	17.5	76.0
200	25.3	71.5
250	28.5	70.0
300	31.5	68.8
400	36.9	67.0
500	41.8	65.5
600	46.3	64.3
1000	62.0	61.0
1200	69.0	59.8

Job Id: **262.1-032576-1**
Certificate No: **TAE00000GE**
Revision No: **2**

Optional: Cold bend per CSA 22.2 @ -40oC and Cold Impact per CSA 22.2 @ -35oC

Application/Limitation

Temperature window

Operation : -40°C to +85 °C

Installation: -15°C to +50°C

In order to achieve a transmission compliant with Category 7 and above, cables shall be installed with suitable termination equipment according to manufacturer's recommendations.

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Datasheets Data transmission cable and system type DB balanced pair non-armored copper cables, - solid conductors rev 09/12 date 2012-06-06

Type test DB1B04R2401 – 9DNV001108 cat 6 stranded
DB2C04S2601 – 9DNV004108 cat 6_A stranded
DB5D04s2601 – 9dnv002108 cat7 stranded
DB5F04S2601 – 9DNV005108 cat 7_A stranded
DB5G04B2201- 9DNV003108 1200MHz solid
DC-W5D04B2303 cat 7 solid dated 2012-04-12
DB-1B04B2303 cat 6 solid, dated 2012-02-05
DB-3C04B2303 cat 6_A solid dated 2012-02-05
DB5F04B2203 cat 7A dated 2011-12-18
Flame test report Category A dated 23.01.2014
9MG0246 Cat 6A Solid armoured Cold bend & Cold Impact dated 18.10.2016
9MGC186 Cat 6 Stranded Cold bend & Cold Impact dated 15.10.2015
9MGC186 Cat 6 Stranded Cold bend & Cold Impact dated 09.03.2016
Mud resistance test NEK 606-2016 dated 15.07.2019.

Tests carried out

Standard	Release	General description	Limitation
IEC 61156-1	2009-10	Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification	
IEC 61156-2	2010-04	Multicore and symmetrical pair/quad cables for digital communications – Part 2: Symmetrical pair/quad cables with transmission characteristics up to 100 MHz - Horizontal floor wiring - Sectional specification	
IEC 61156-3	2008-11	Multicore and symmetrical pair/quad cables for digital communications – Part 3: Work area cable - Sectional specification	

Job Id: **262.1-032576-1**
Certificate No: **TAE00000GE**
Revision No: **2**

IEC 61156-5	2012-12	Multicore and symmetrical pair/quad cables for digital communications – Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Horizontal floor wiring – Sectional specification	
IEC 61156-6	2012-12	Multicore and symmetrical pair/quad cables for digital communications - Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Work area wiring - Sectional specification	Reference to requirement for category cable: 6 (250MHz), 6A (500 MHz), 7 (600MHz), 7A (1000 MHz)
IEC 61156-7	2012-12	Multicore and symmetrical pair/quad cables for digital communications – Part 7: Symmetrical pair cables with transmission characteristics up to 1 200 MHz - Sectional specification for digital and analog communication cables	
IEC 61156-8	2013-05	Multicore and symmetrical pair/quad cables for digital communications – Part 8: Symmetrical pair/quad cables with transmission characteristics up to 1 200 MHz – Work area wiring – Sectional specification	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
IEC 60332-3-22	2018-07	Tests on electric cables under fire conditions - Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables - Category A	Charred portion of sample does not exceed 2,5m above bottom edge of burner.
IEC 60332-3-24	2018-07	Tests on electric and optical fibre cables under fire conditions - Part 3-24: Test for vertical flame spread of vertically-mounted bunched wires or cables - Category C	Charred portion of sample does not exceed 2,5m above bottom edge of burner.
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables – Determination of the amount of halogen acid gas	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables – Determination of the degree of acidity of gases evolved during the combustion of materials taken from electric cables by measuring pH and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS

Job Id: **262.1-032576-1**
 Certificate No: **TAE00000GE**
 Revision No: **2**

IEC 61034-1/2	2013-07/09	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke
IEC 60332-1-1/2/3	2015-07	Tests on electric and optical fibre cables under fire conditions Test for vertical flame propagation for a single small insulated wire or cable	
NEK 606 Ed. 5	2016	Cables for offshore installations. Halogen-free and/or mud resistant. Technical specification.	Mud resistance test: Required Max variations \pm : <u>IRM902 & 903 100°C 7d.</u> TS & E@B, weight & vol.: \pm 30% <u>Calc. Bromide 70°C 56d.</u> TS & E@B: \pm 25%, weight: \pm 15%, vol.: \pm 20% <u>Oil based mud:</u> <u>EDC 95/11 70°C 56d</u> TS & E@B \pm 30%, weight & vol.: \pm 25%
IEC 60092-350	2014-08	Annex E: Cold bend test and impact test for low temperature behaviour	Cold bend: -40°C Cold impact: -35°C
CSA C22.2 No. 03	2009	Flexibility at any specified temp.	Cold bend: -40°C
CSA C22.2 No. 03	2009	Abnormal low temperature – impact	Cold impact: -35°C

Marking of product

TELDOR MG No. of cores x No. of pairs, Cross-section, Type P/N, meter mark – IEC 60332-22 OR IEC 60332-2-2 – LOT No.

Family	TYPE	Transmission Properties	Pair Count	Solid Cond.	AWG	Flame Rating	Options
MGD	2=F/UTP 3=SF/UTP 4=U/FTP 5=F/FTP 6=S/FTP 7=SF/FTP	3=CAT3 5=CAT5 E=CAT5e B=CAT 6 C=CAT 6A D=CAT 7 F=CAT 7A G=1200MHz	NN Core count in multi cables	B=BC Solid (bare copper) T=TC Solid (tinned copper)	26=26AWG 24=24AWG 23=23AWG 22=22AWG	A=IEC60332-3-22 (Cat.A) C=IEC60332-3-24 (Cat.C)	XX Alpha numeric

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)

Job Id: **262.1-032576-1**
Certificate No: **TAE00000GE**
Revision No: **2**

- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE