

Cat.7 4x2x23/1 S/FTP LSZH-SHF1

Part Number: **9MG0543xxx**


Applications: Offshore installations, Maritime Environment, Indoor use, fixed installations, High data rates, Ships, High speed & Light craft

General Construction: Category 7 , S/FTP, SHF1 marine type cable constructed with 4 individually foil-shielded twisted pairs with solid conductors, cabled together, overall braid-shield and jacketed.
 The cable is certified by DNV / DNV-GL FILE NO. E-13122 and by ABS FILE NO. 14-GE1164406-1.

Outer Jacket Material: FR-LSZH

Outer Diameter: 7.9 mm nom.

Weight: 70 kg/km



Design & Materials

Conductor Material:	Annealed Bare Copper
Conductor Size:	23 AWG
Conductor Construction:	Solid
Insulation Material:	Cellular PO
Insulation O.D.:	1.38 mm nom.
Conductor unit identification:	Solid Color
Color code:	Per TIA/EIA 568-B
Ind. Shield Material:	Aluminum/Polyester Foil
Ind. Shield Design:	Helically applied Aluminum foil, 100% coverage
Conductor unit lay-up:	Pairs
Overall Shield Design:	Braid
Overall Braid Material:	Annealed Tinned Copper
Braid Coverage:	55 % nom.
Overall Drain-wire Material:	Annealed Tinned Copper
Overall Drain-wire size:	0.41 mm
Overall Drain-wire Construction:	Solid
Total number of conductors:	8
Outer Jacket Color:	See TELDOR Jacket Code
Marking:	Per request, Teldor Standard

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Standards

Applicable Standards:	IEC 60092-359, IEC 60092-350, IEC 61156-5, IEEE 802.3at (PoE+), ISO/IEC 11801, RoHS-2 2011/65/EU
Flamability Rating:	IEC 60332-1, IEC 60332-3-22, IEC 60332-3, IEC 60754-2, IEC 61034-1/2, UL 1581 VW-1

Electrical Properties:

Cat. 7 Horizontal Cables *

Freq. MHz	Attenuation dB/100m 20°C		PS NEXT Loss dB		NEXT Loss dB		RL dB		PS ANEXT dB		PS ELFEXT dB		ELFEXT dB	
	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7
1	2.0	2.0	105.0	75.0	108.0	78.0	22.0	20.0	68.0	N/A	95.0	75.0	98.0	78.0
4	3.6	3.7	98.0	75.0	101.0	78.0	25.0	23.0	68.0	N/A	90.0	75.0	93.0	78.0
10	5.6	5.8	95.0	75.0	98.0	78.0	28.0	25.0	68.0	N/A	86.0	71.0	89.0	74.0
20	7.9	8.3	90.0	75.0	93.0	78.0	28.0	25.0	68.0	N/A	80.0	65.0	83.0	68.0
30	9.7	10.2	85.0	75.0	88.0	78.0	27.0	23.8	68.0	N/A	76.0	61.5	79.0	64.5
100	18.0	19.0	80.0	69.4	83.0	72.4	24.0	21.1	68.0	N/A	66.0	51.0	69.0	54.0
150	22.4	23.6	78.0	66.7	81.0	69.7	22.0	18.8	65.0	N/A	63.0	47.5	66.0	50.5
200	26.0	27.5	78.0	65.0	81.0	68.0	21.0	18.0	65.0	N/A	60.0	45.0	63.0	48.0
250	29.4	31.0	75.0	63.4	78.0	66.4	20.0	17.3	62.0	N/A	58.0	43.0	61.0	46.0
300	32.5	34.2	75.0	62.2	78.0	65.2	19.0	17.3	62.0	N/A	52.0	41.5	55.0	44.5
400	38.0	40.0	70.0	60.4	73.0	63.4	19.0	17.3	62.0	N/A	49.0	38.9	52.0	41.9
500	43.0	45.2	70.0	58.9	73.0	61.9	19.0	17.3	62.0	N/A	47.0	37.0	50.0	40.0
600	47.6	50.1	70.0	57.7	73.0	60.7	19.0	17.3	62.0	N/A	45.0	35.4	48.0	38.4

* Supplied cables meet the minimum Cat. 7 transmission requirements as per IEC 61156-5 Ed. 2

Performance

Frequency Range:	1 - 600 MHz
Impedance:	100
Transfer Impedance:	Grade 1
Coupling Attenuation:	Type I
DC Resistance:	73 /km nom.
Max. Resistance Unbalance:	2 %
Capacitance Unbalance:	1.2 pF/m max.
Velocity of Propagation:	78 % nom.
Propagation Delay Skew:	25 ns/100m max.
Dielectric Strength:	700 V/minute
Dielectric Strength to Shield:	700 V/minute
Min. Insulation Resistance :	5 G •km
Tensile Strength - Short Term:	130 N max.
Min. Bend Radius:	80 mm
Max. Operating Temperature:	+ 85 °C
Min. Operating Temperature:	- 40 °C
UV resistance:	Yes

Prepared By	Revised By	Version Num	Modified on
Asher Bohbut	Asher Bohbut	1.7	25-06-2015

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.