



CABLE STRUCTURE

Conductor	Electrolytic, stranded, annealed copper wire IEC 60228 Class 2 (Class 5 and / or tinned on request)
Insulation	Cross linked polyethylene compound (XLPE).
Inner Covering	Separating foil and / or halogen-free compound
Screen	Copper / polyester tape coverage 100% and copper wire braided screen min.coverage 90% (Tinned copper wire braid on request)
Outer sheath	Halogen-free, flame retardant, polyolefin based compound (SHFI).
Color	Black or Grey.

STANDARDS & MAIN CHARACTERISTICS

Construction	IEC 60092 / 353
Tests And Material	IEC 60092 / 350-360
Flame Retardant	IEC 60332 / 1-2, IEC 60332 / 3-22 Cat A
Halogen Content	IEC 60754 / 1-2
Smoke Emission	IEC 61034 / 1-2 (DIN EN 50268 / 1-2)
Ozon Resistance	IEC 60811 / 403
Shielding Effectiveness (For Emc Type)	DIN EN 50147-1
Working Temperature	-40°C / + 90°C
Min. Bending Radius (fixed)	6 x D
Rated Voltage	1,8 / 3 (3,6) kV
Test Voltage	6,5 kV

Minimum recommended installation temperature -15°C

For core identification, diameter tolerances and current ratings etc. see technical information section

Application

Used as fixed installation cables in various electromechanical and electronic equipments. Due to its' overall screen the electromagnetic interference is minimized. It can be used as motor supply cable and for frequency converters controlled low voltage AC drives on ships, called VFD applications.



Halogen
Free



Low Smoke
Density



Flame
Retardant



Rated
Voltage



Test
Voltage



Working
Temperature



Bending
Radius



No
Corrosivity

Cross Section (mm ²)	Nominal Overall Diameter (mm)	Approximate Weight (kg / km)	Min. Bending Radius Fixed Installed (mm)	Max Resistance of Conductors at 20°C (ohm / km)	Current Carrying Capacity at 45°C (A)
1x10	13,0	295	78	1,83	72
1x16	14,6	411	88	1,15	96
1x25	15,7	512	95	0,727	127
1x35	17,2	631	103	0,524	157
1x50	18,5	791	111	0,387	196
1x70	20,2	1022	121	0,268	242
1x95	22,3	1324	134	0,193	293
1x120	23,8	1585	143	0,153	339
1x150	25,7	1908	154	0,124	389
1x185	27,8	2315	167	0,0991	444
1x240	30,4	2919	183	0,0754	522
3x10	23,4	933	140	1,83	50
3x16	25,8	1214	155	1,15	67
3x25	28,3	1564	170	0,727	89
3x35	31,3	1950	188	0,524	110
3x50	34,7	2540	208	0,387	137
3x70	38,7	3400	232	0,268	169
3x95	43,0	4390	258	0,193	205
3x120	47,1	5382	283	0,153	237
3x150	50,9	6464	305	0,124	272
3x185	53,8	7928	323	0,0991	311
3x240	63,3	9480	380	0,0754	365