

RFOU(I) - NEK 606 (S1/S5/S101)

HALOGEN FREE, FLAME RETARDANT, INDIVIDUALLY SCREENED INSTRUMENTATION CABLES



CABLE DESCRIPTION

Tinned Copper Class 2 or 5 Flexible Conductors, EPR insulated, Individual foil screen + DW, LSOH, Tinned Copper Wire Braid, LSOH MUD RESISTANT Grey or Blue; NEK606; IEC60092-376; IEC60092-350-351-359; IEC60754 1-2; IEC60754 1-2; IEC61034 1-2; IEC60332-1 IEC60332-3 CAT A; Voltage Rating 150/250V; Minimum Bending Radius 8xOD

APPLICATION

These cables are used for fixed installations on open deck in ships and offshore units

Gland sizes shown are only provided as a guide

CSWL Part No	Number Pairs/Triples	Size mm ²	OD (mm)		Weight KG/KM	Gland Size (Hawke)		SHEATH COLOUR
			Nominal					
CSW0.75MM1PRRFOUIGY	1PR	0.75	10.3		160	Univ OS	20mm (SS)	GREY
CSW0.75MM1PRRFOUIBU	1PR	0.75	10.3		160	Univ OS	20mm (SS)	BLUE
CSW0.75MM2PRRFOUIGY	2PR	0.75	14.9		300	Univ O	20mm (S)	GREY
CSW0.75MM2PRRFOUIBU	2PR	0.75	14.9		300	Univ O	20mm (S)	BLUE
CSW0.75MM4PRRFOUIGY	4PR	0.75	19.6		580	Univ A	20mm	GREY
CSW0.75MM4PRRFOUIBU	4PR	0.75	19.6		580	Univ A	20mm	BLUE
CSW0.75MM8PRRFOUIGY	8PR	0.75	23.4		800	Univ B	25mm	GREY
CSW0.75MM8PRRFOUIBU	8PR	0.75	23.4		800	Univ B	25mm	BLUE
CSW0.75MM12PRRFOUIGY	12PR	0.75	25.1		900	Univ C	32mm	GREY
CSW0.75MM12PRRFOUIBU	12PR	0.75	25.1		900	Univ C	32mm	BLUE
CSW0.75MM16PRRFOUIGY	16PR	0.75	27.7		1100	Univ C	32mm	GREY
CSW0.75MM16PRRFOUIBU	16PR	0.75	27.7		1100	Univ C	32mm	BLUE
CSW0.75MM24PRRFOUIGY	24PR	0.75	32.8		1590	Univ C2	40mm	GREY
CSW0.75MM24PRRFOUIBU	24PR	0.75	32.8		1590	Univ C2	40mm	BLUE
<i>Gland sizes shown are only provided as a guide</i>								
CSW1.5MM1PRRFOUIGY	1PR	1.5	11.7		210	Univ O	20mm (S)	GREY
CSW1.5MM1PRRFOUIBU	1PR	1.5	11.7		210	Univ O	20mm (S)	BLUE
CSW1.5MM2PRRFOUIGY	2PR	1.5	17.4		400	Univ A	20mm	GREY
CSW1.5MM2PRRFOUIBU	2PR	1.5	17.4		400	Univ A	20mm	BLUE
CSW1.5MM4PRRFOUIGY	4PR	1.5	19.9		580	Univ A	20mm	GREY
CSW1.5MM4PRRFOUIBU	4PR	1.5	19.9		580	Univ A	20mm	BLUE
CSW1.5MM8PRRFOUIGY	8PR	1.5	28.1		1110	Univ C	32mm	GREY
CSW1.5MM8PRRFOUIBU	8PR	1.5	28.1		1110	Univ C	32mm	BLUE

A Dron & Dickson Group Company



Cable Solutions

WORLDWIDE

HALOGEN FREE, FLAME RETARDANT, INDIVIDUALLY SCREENED INSTRUMENTATION CABLES

Gland sizes shown are only provided as a guide

CSWL Part No	Number Pairs/Triples	Size mm2	OD (mm) Nominal	Weight KG/KM	Gland Size (Hawke)		SHEATH COLOUR
CSW1.5MM12PRRFOUIGY	12PR	1.5	30.3	1200	Univ C	32mm	GREY
CSW1.5MM12PRRFOUIBU	12PR	1.5	30.3	1200	Univ C	32mm	BLUE
CSW1.5MM16PRRFOUIGY	16PR	1.5	34.0	1660	Univ C2	40mm	GREY
CSW1.5MM16PRRFOUIBU	16PR	1.5	34.0	1660	Univ C2	40mm	BLUE
CSW1.5MM24PRRFOUIGY	24PR	1.5	40.4	2400	Univ D	50mm	GREY
CSW1.5MM24PRRFOUIBU	24PR	1.5	40.4	2400	Univ D	50mm	BLUE
<i>Gland sizes shown are only provided as a guide</i>							
CSW2.5MM1PRRFOUIGY	1PR	2.5	12.7	260	Univ O	20mm (S)	GREY
CSW2.5MM1PRRFOUIBU	1PR	2.5	12.7	260	Univ O	20mm (S)	BLUE
<i>Gland sizes shown are only provided as a guide</i>							
CSW0.75MM1TRRFOUIGY	1TR	0.75	10.7	180	Univ OS	20mm (SS)	GREY
CSW0.75MM1TRRFOUIBU	1TR	0.75	10.7	180	Univ OS	20mm (SS)	BLUE
CSW0.75MM2TRRFOUIGY	2TR	0.75	16.2	360	Univ A	20mm	GREY
CSW0.75MM2TRRFOUIBU	2TR	0.75	16.2	360	Univ A	20mm	BLUE
CSW0.75MM4TRRFOUIGY	4TR	0.75	18.4	500	Univ A	20mm	GREY
CSW0.75MM4TRRFOUIBU	4TR	0.75	18.4	500	Univ A	20mm	BLUE
CSW0.75MM8TRRFOUIGY	8TR	0.75	25.9	870	Univ C	32mm	GREY
CSW0.75MM8TRRFOUIBU	8TR	0.75	25.9	870	Univ C	32mm	BLUE
CSW0.75MM12TRRFOUIGY	12TR	0.75	27.8	1110	Univ C	32mm	GREY
CSW0.75MM12TRRFOUIBU	12TR	0.75	27.8	1110	Univ C	32mm	BLUE
<i>Gland sizes shown are only provided as a guide</i>							
CSW1.5MM1TRRFOUIGY	1TR	1.5	12.2	240	Univ O	20mm (S)	GREY
CSW1.5MM1TRRFOUIBU	1TR	1.5	12.2	240	Univ O	20mm (S)	BLUE
CSW1.5MM2TRRFOUIGY	2TR	1.5	19.0	480	Univ A	20mm	GREY
CSW1.5MM2TRRFOUIBU	2TR	1.5	19.0	480	Univ A	20mm	BLUE
CSW1.5MM4TRRFOUIGY	4TR	1.5	21.9	710	Univ B	25mm	GREY
CSW1.5MM4TRRFOUIBU	4TR	1.5	21.9	710	Univ B	25mm	BLUE
CSW1.5MM8TRRFOUIGY	8TR	1.5	31.3	1060	Univ C	32mm	GREY
CSW1.5MM8TRRFOUIBU	8TR	1.5	31.3	1060	Univ C	32mm	BLUE
CSW1.5MM12TRRFOUIGY	12TR	1.5	34.2	1800	Univ C2	40mm	GREY
CSW1.5MM12TRRFOUIBU	12TR	1.5	34.2	1800	Univ C2	40mm	BLUE

Pair - Black - Light Blue

Triple - Black - Light Blue - Brown

Quad - Black - Light Blue - Brown - Grey

