

# BFOU(I) - NEK 606 (S3/S7/S103)

HALOGEN FREE, FIRE RESISTANT, FLAME RETARDANT, INDIVIDUALLY SCREENED INSTRUMENTATION CABLES



## CABLE DESCRIPTION

Tinned Copper Class 2 or 5 Flexible Conductors, Mica Glass Taped, EPR insulated, Individual foil screen + DW, LSOH, Tinned Copper Wire Braid, LSOH MUD RESISTANT Grey or Blue; NEK606; IEC60092-376; IEC60092-350-351-359; IEC60754 1-2; IEC60754 1-2; IEC61034 1-2; IEC60331; IEC60332-1 IEC60332-3 CAT A; Voltage Rating 150/250V; Minimum Bending Radius 8xOD

## APPLICATION

These cables are used for fixed installations in all areas and on open deck in ships and offshore units

*Gland sizes shown are only provided as a guide*

CSWL Part No	Number Pairs/Triples	Size mm <sup>2</sup>	OD (mm) Nominal	Weight KG/KM	Gland Size (Hawke)		SHEATH COLOUR
					Univ	Size	
CSW0.75MM1PRBFOUISGY	1PR	0.75	11.6	210	Univ O	20mm	GREY
CSW0.75MM1PRBFOUISBU	1PR	0.75	11.6	210	Univ O	20mm	BLUE
CSW0.75MM2PRBFOUISGY	2PR	0.75	17.1	330	Univ A	20mm	GREY
CSW0.75MM2PRBFOUISBU	2PR	0.75	17.1	330	Univ A	20mm	BLUE
CSW0.75MM4PRBFOUISGY	4PR	0.75	19.6	450	Univ B	25mm	GREY
CSW0.75MM4PRBFOUISBU	4PR	0.75	19.6	450	Univ B	25mm	BLUE
CSW0.75MM8PRBFOUISGY	8PR	0.75	27.7	730	Univ C	32mm	GREY
CSW0.75MM8PRBFOUISBU	8PR	0.75	27.7	730	Univ C	32mm	BLUE
CSW0.75MM12PRBFOUISGY	12PR	0.75	29.8	960	Univ C2	40mm	GREY
CSW0.75MM12PRBFOUISBU	12PR	0.75	29.8	960	Univ C2	40mm	BLUE
CSW0.75MM16PRBFOUISGY	16PR	0.75	33.4	1450	Univ C2	40mm	GREY
CSW0.75MM16PRBFOUISBU	16PR	0.75	33.4	1450	Univ C2	40mm	BLUE
CSW0.75MM24PRBFOUISGY	24PR	0.75	39.7	1710	Univ D	50mm	GREY
CSW0.75MM24PRBFOUISBU	24PR	0.75	39.7	1710	Univ D	50mm	BLUE
<i>Gland sizes shown are only provided as a guide</i>							
CSW1.5MM1PRBFOUISGY	1PR	1.5	13.0	240	Univ O	20mm	GREY
CSW1.5MM1PRBFOUISBU	1PR	1.5	13.0	240	Univ O	20mm	BLUE
CSW1.5MM2PRBFOUISGY	2PR	1.5	19.6	430	Univ B	25mm	GREY
CSW1.5MM2PRBFOUISBU	2PR	1.5	19.6	430	Univ B	25mm	BLUE
CSW1.5MM4PRBFOUISGY	4PR	1.5	22.6	610	Univ B	25mm	GREY
CSW1.5MM4PRBFOUISBU	4PR	1.5	22.6	610	Univ B	25mm	BLUE
CSW1.5MM8PRBFOUISGY	8PR	1.5	32.8	1140	Univ C2	40mm	GREY
CSW1.5MM8PRBFOUISBU	8PR	1.5	32.8	1140	Univ C2	40mm	BLUE

A Dron & Dickson Group Company

**Cable Solutions**

WORLDWIDE

**HALOGEN FREE, FIRE RESISTANT, FLAME RETARDANT, INDIVIDUALLY SCREENED INSTRUMENTATION CABLES**

*Gland sizes shown are only provided as a guide*

CSWL Part No	Number Pairs/Triples	Size mm <sup>2</sup>	OD (mm) Nominal	Weight KG/KM	Gland Size (Hawke)		SHEATH COLOUR
CSW1.5MM12PRBFOUISGY	12PR	1.5	35.4	1300	Univ C2	40mm	GREY
CSW1.5MM12PRBFOUISBU	12PR	1.5	35.4	1300	Univ C2	40mm	BLUE
CSW1.5MM16PRBFOUISGY	16PR	1.5	39.7	1850	Univ D	50mm	GREY
CSW1.5MM16PRBFOUISBU	16PR	1.5	39.7	1850	Univ D	50mm	BLUE
CSW1.5MM24PRBFOUISGY	24PR	1.5	47.2	2520	Univ D	50mm	GREY
CSW1.5MM24PRBFOUISBU	24PR	1.5	47.2	2520	Univ D	50mm	BLUE
<i>Gland sizes shown are only provided as a guide</i>							
CSW2.5MM1PRBFOUISGY	1PR	2.5	14.4	290	Univ A	20mm	GREY
CSW2.5MM1PRBFOUISBU	1PR	2.5	14.4	290	Univ A	20mm	BLUE
<i>Gland sizes shown are only provided as a guide</i>							
CSW0.75MM1TRBFOUISGY	1TR	0.75	12.1	230	Univ O	20mm (S)	GREY
CSW0.75MM1TRBFOUISBU	1TR	0.75	12.1	230	Univ O	20mm (S)	BLUE
CSW0.75MM2TRBFOUISGY	2TR	0.75	18.7	390	Univ A	20mm	GREY
CSW0.75MM2TRBFOUISBU	2TR	0.75	18.7	390	Univ A	20mm	BLUE
CSW0.75MM4TRBFOUISGY	4TR	0.75	21.5	540	Univ B	25mm	GREY
CSW0.75MM4TRBFOUISBU	4TR	0.75	21.5	540	Univ B	25mm	BLUE
CSW0.75MM8TRBFOUISGY	8TR	0.75	30.7	910	Univ C	32mm	GREY
CSW0.75MM8TRBFOUISBU	8TR	0.75	30.7	910	Univ C	32mm	BLUE
CSW0.75MM12TRBFOUISGY	12TR	0.75	33.6	1680	Univ C2	40mm	GREY
CSW0.75MM12TRBFOUISBU	12TR	0.75	33.6	1680	Univ C2	40mm	BLUE
<i>Gland sizes shown are only provided as a guide</i>							
CSW1.5MM1TRBFOUISGY	1TR	1.5	14.0	270	Univ A	20mm	GREY
CSW1.5MM1TRBFOUISBU	1TR	1.5	14.0	270	Univ A	20mm	BLUE
CSW1.5MM2TRBFOUISGY	2TR	1.5	21.6	510	Univ B	25mm	GREY
CSW1.5MM2TRBFOUISBU	2TR	1.5	21.6	510	Univ B	25mm	BLUE
CSW1.5MM4TRBFOUISGY	4TR	1.5	25.0	760	Univ C	32mm	GREY
CSW1.5MM4TRBFOUISBU	4TR	1.5	25.0	760	Univ C	32mm	BLUE
CSW1.5MM8TRBFOUISGY	8TR	1.5	37.0	1090	Univ C2	40mm	GREY
CSW1.5MM8TRBFOUISBU	8TR	1.5	37.0	1090	Univ C2	40mm	BLUE
CSW1.5MM12TRBFOUISGY	12TR	1.5	39.9	1900	Univ D	50mm	GREY
CSW1.5MM12TRBFOUISBU	12TR	1.5	39.9	1900	Univ D	50mm	BLUE

Pair - Black - Light Blue

Triple - Black - Light Blue - Brown

Quad - Black - Light Blue - Brown - Grey

